

# Data Sheet



南方水泵选型资料

CHL 卧式轻型离心泵



## 技术参数:

流量: 0.5m<sup>3</sup>/h~32m<sup>3</sup>/h;

扬程: 5m~88m;

功率: 0.37kW~7.5kW;

液体温度: -15℃~+105℃;

频率: 50Hz/60Hz;

## 应用范围:

工业清洗, 供水和增压, 空调系统, 冷却系统, 净水处理;

## 南方水泵选型表 (CHL 卧式轻型离心泵)

序号	货号	型号	功率(kw)	序号	货号	型号	功率(kw)
1	00656	CHL 2-10	0.37	16	001780	CHL12-10	0.75
2	00761	CHL 2-20	0.37	17	001891	CHL12-20	1.2
3	00841	CHL 2-30	0.55	18	002372	CHL12-30	1.8
4	00931	CHL 2-40	0.55	19	002600	CHL12-40	2.4
5	001120	CHL 2-50	0.55	20	003056	CHL12-50	3
6	001156	CHL 2-60	0.75				
7	00775	CHL 4-10	0.55	21	002113	CHL 16-10	1.1
8	00832	CHL 4-20	0.55	22	002295	CHL 16-20	2.2
9	00970	CHL 4-30	0.75	23	002802	CHL 16-30	3.0
10	001071	CHL 4-40	0.75				
				24	002181	CHL20-10	1.1
11	001682	CHL 8-10	0.75	25	002400	CHL20-20	2.2
12	001749	CHL 8-20	0.75	26	003365	CHL20-30	4.0
13	001888	CHL 8-30	1.1				
14	001966	CHL 8-40	1.5				
15	002340	CHL 8-50	2.2				